

Go-Devil Drop Bar

DESCRIPTION

The **Go-Devil Drop Bar** is designed with a pointed bottom that is required to mechanically break the disk(s) in Single and Dual Magnumdisks™. All Go-Devil Drop Bars are manufactured with standard fish neck sizes if it becomes necessary to fish the bar.

**NOTE: For larger I.D. tubulars, custom "Finned" Go-Devil Drop Bars available upon request.*

FEATURES

- Brass construction
- 1" OD on standard Magnumdisk™ applications
- Allows for safe rupturing of Magnumdisk™ with high differential
- May be run in any environment and depth
- **Go-Devil** may be lubricated in the top of the tree and dropped by opening the tree valve
- Length of bar will vary upon depth of Magnumdisk™
- Pointed impact point for more efficient shattering
- Economical alternative to coil tubing or slick line shattering
- Shatters the ceramic disk into small crushable fragments



NOTE: Length of Go-Devil will vary according to depth, well bore fluid weight and deviation. If deviation of well is 55° or greater - do not use Go-Devil Drop Bar.

PART NUMBER	DESCRIPTION	WEIGHT OF BAR	FLUID	DRY	FISHING NECK	O.D.
09.DBGD.100.0178	GO-DEVIL, 1.00"OD x 18"LG x 7/8" Fish Neck	4 lbs	N/A	0'-7,000'	1.000"	1.000"
09.DBGD.100.0378	GO-DEVIL, 1.00"OD x 36"LG x 7/8" Fish Neck	8 lbs	0'-3,000'	0'-10,000'	1.000"	1.000"
09.DBGD.100.0478	GO-DEVIL, 1.00"OD x 48"LG x 7/8" Fish Neck	10.5 lbs	0'-5,000'	0'-10,000'	1.000"	1.000"
09.DBGD.100.0878	GO-DEVIL, 1.00"OD x 96"LG x 7/8" Fish Neck	26.25 lbs	0'-10,000'	10,000' - +	1.000"	0.875"
09.DBGD.100.1078	GO-DEVIL, 1.00"OD x 120"LG x 7/8" Fish Neck	31.5 lbs	10,000' - +	10,000' - +	1.000"	0.875"