



A-1 HYDRAULIC™

INNOVATION REVEALED

The A-1 Hydraulic Setting Tool is utilized to set bridge plugs, composite plugs, packers and cement retainers by converting applied hydraulic pressure into a pull force.

The setting tool is deployed into the well by using coiled tubing, tubing or drill pipe.

FEATURES

- Automatically balances with wellbore fluid
- Hydraulically activated by applied pressure
- No ballistics required
- Redress kits available
- Will couple to most adapter kits
- No wet string pull outs
- Coil tubing, tubing or drill pipe conveyed
- Four stages are standard (Five stages on the 1.750" tool)
- Can withstand high tensile loads
- No rotation required

OPERATIONS

While running into the well, the tool automatically fills with wellbore fluid and remains balanced. When the setting depth is reached, a ball bearing is released down the work string. A circulation rate can then be established to aid in pumping the ball bearing down into its mating seat inside the setting tool. When the ball bearing is fully seated, a pressure build up will be noted. Slowly continue applying the required pressure to fully stroke the setting tool and set the down hole device. After the tool is fully stroked, circulation will be re-established.



Setting Tools

1.75 SETTING TOOL: BAKER #05 EQUIVALENT

Piston Area: 0.89 in² (575.5mm²) /cylinder effective surface area
 4.46 in² (2,877.5mm²) with 5 stages

Set Screw Shear Value: 4 stage: 275 PSI/screw; 5 stage: 225 PSI/screw

Example: Applied PSI (MPa) @ surface X total x-sectional area = shear value Lbs (Kgs) @ tool
 2,800psi (19.3MPa) X 4.46 in² (2,877.5 mm²) = 12,488lbs (5,664.6Kg)

2.50 SETTING TOOL: BAKER #10 EQUIVALENT

Piston Area: 2.05 in² (1,320.0mm²) /cylinder effective surface area
 8.18 in² (5,280.0mm²) with 4 stages

Set Screw Shear Value: 4 stage: 125 PSI/screw; 5 stage: 100 PSI/screw

Example: Applied PSI (MPa) @ surface X total x-sectional area = shear value Lbs (Kgs) @ tool
 4,000psi (27.6MPa) X 8.184 in² (5,280.0mm²) = 32,736lbs (14,848.8Kg)

3.13 SETTING TOOL: BAKER #10 EQUIVALENT

Piston Area: 3.30 in² (2,127.7mm²) /cylinder effective surface area
 13.19 in² (8,511.0mm²) with 4 stages

Set Screw Shear Value: 4 stage: 175 PSI/screw; 5 stage: 140 PSI/screw

Example: Applied PSI (MPa) @ surface X total x-sectional area = shear value Lbs (Kgs) @ tool
 2,500psi (17.2MPa) X 13.192 in² (8,511.0mm²) = 32,980lbs (14,959.5Kg)

3.13 SETTING TOOL: BAKER #20 EQUIVALENT

Piston Area: 3.30 in² (2,127.7mm²) /cylinder effective surface area
 13.192 in² (8,511.0mm²) with 4 stages

Set Screw Shear Value: 4 stage: 175 PSI/screw; 5 stage: 140 PSI/screw

Example: Applied PSI (MPa) @ surface X total x-sectional area = shear value Lbs (Kgs) @ tool
 3,800psi (26.2MPa) X 13.192 in² (8,511.0mm²) = 50,130lbs (22,739Kg)

3.63 SETTING TOOL: BAKER #20 EQUIVALENT

Piston Area: 5.31 in² (3,423.9 mm²)/cylinder effective surface area
 21.23 in² (13,694.8 mm²) with 4 stages

Set Screw Shear Value: 4 stage: 170 PSI/screw; 5 stage: 212 PSI/screw

Example: Applied PSI (MPa) @ surface X total x-sectional area = shear value lbs (Kgs) @ tool
 2,500psi (17.2MPa) X 21.23 in² (13,694.8mm²) = 53,067lbs (24,071Kg)

4.75 SETTING TOOL: BAKER #20 EQUIVALENT

Piston Area: 10.90 in² (7011.9 mm²) / cylinder effective surface area
 21.74 in² (14,063.7 mm²) with 2 stages; 32.605 in² (21,035.6 mm²) with 3 stages

Set Screw Shear Value: 2 stage 125 PSI/screw; 3 stage: 80 PSI/screw

Examples: Applied PSI (MPa) @ surface X total x-sectional area = shear value Lbs (Kgs) @ tool
 2,530 PSI (17.4 MPa) X 21.737 in² (14,063.7 mm²) = 55,000 Lbs (24,948Kgs)
 with 2 stages 1,685 PSI (11.6 MPa) X 32.605 in² (21,035.6 mm²) = 55,000 Lbs (24,948Kgs) with 3 stages

O.D. Size inch (mm)	Standard Connection inch (mm)	Length inch (mm)	Ball Seat inch (mm)	Stroke inch (mm)	Temp Rating
1.75 (44.5)	1.0 (25.4) CS HYDRIL	83 (2,133.6)	0.250 (6.4)	7.0 (177.8)	400 °F (204 °C)
2.50 (63.5)	1-1/2" (52.4) MT	92.50 (2,349.5)	0.44 (11.1)	10.0 (254.0)	400 °F (204 °C)
3.13 (79.4)	2-3/8" (60.3) EU 8RD	84.32 (2,141.7)	0.44 (11.1)	8.75 (222.3)	400 °F (204 °C)
3.63 (92.1)	2-3/8" (60.3) EU 8RD	84.31 (2,141.5)	0.44 (11.1)	9.50 (241.3)	400 °F (204 °C)
4.75 (120.7)	2-7/8" (73.0) EU 8RD	56.50 (1,435.0)	0.75 (19.1)	12.0 (304.9)	400 °F (204 °C)

For more information, and to find a representative near you, visit www.magnumoiltools.com.

Copyright © 2018 Magnum Oil Tools International, Ltd. All Rights Reserved.

REV - May 22, 2018 10:18 AM

This presentation contains proprietary and/or confidential information that is the exclusive and sole property of Magnum Oil Tools International, Ltd. The presentation also includes information that contains intellectual property rights owned by and/or assigned to Magnum Oil Tools International, Ltd. The information from the presentation shall not be disclosed to any third party without express written consent from Magnum Oil Tools International, Ltd. prior to disclosure.