



MAGNUM SERIES CCR™

INNOVATION REVEALED

The **Magnum Series™ Composite Cement Retainer** utilizes a built-in sliding sleeve assembly for remedial cementing or zone abandonment. The sliding sleeve is operated by a stinger assembly from the surface. Because of its low metallic content, the **Magnum Series™ Composite Cement Retainer** is quickly milled and circulated back to surface using conventional milling, drilling with a rig and tubing or with coiled tubing.

FEATURES

- Consistent drill times of 30 minutes or less
- Can be set on wireline or coiled tubing using conventional setting tools
- Can be milled or drilled with coiled tubing or a rig
- Positive seal after setting
- Millable cast iron slips
- High differential pressure rating
- Low temp and high temp materials conducive to a wide range of environments
- Patented precision shearing device
- Magnum Series™ is set via a universal setting sleeve and adapter
- Simple valve control by surface pressure manipulation
- Also available in Poppet Style
- Can be converted to a Magnum Series™ Ball Drop, Bridge, Flo-Back,
- Flo-Back with Bio-Ball Plug
- Patent Pending



Sliding Sleeve
Bottom



Composite Cement Retainers

OPERATIONS

Once the Magnum Series™ Composite Cement Retainer is set, a stinger assembly is attached to the workstring and run to retainer depth. The stinger is then inserted into the retainer bore, sealing against the mandrel I.D. and isolating the workstring from the upper annulus. Once sufficient set down weight has been applied, the stinger assembly will open the lower sliding sleeve, allowing the squeeze operation to be performed.

CASING SPECS		RETAINER SPECS						OPERATING RANGES			
CASING O.D. inch (mm)	WEIGHT RANGE lb/ft (kg/m)	O.D. inch (mm)	STINGER		SLIDING SLEEVE	LENGTH inch (mm)	SETTING TOOL	LOW TEMP/ LOW PSI	LOW TEMP/ HIGH PSI	MID TEMP/ HIGH PSI	HI TEMP/ HIGH PSI
			MIN ID inch (mm)	FLOW AREA inch ² (mm ²)	FLOW AREA inch ² (mm ²)						
4 (101.6)	9.5-11.0 (14.1-16.4)	3.19 (81.0)	0.75 (19.1)	0.44 (11.2)	1.23 (31.2)	28.6 (726.4)	Magnum "A-1", Baker #10 or Owen	250°F 8KSI (121°C) (55.2MPa)	250°F 10KSI (121°C) (68.9MPa)	300°F 10KSI (149°C) (68.9MPa)	375°F 10KSI (191°C) (68.9MPa)
4-1/2 (114.3)	9.5-13.5 (14.1-20.1)	3.57 (90.7)									
5 (127.0)	15.1-17.1 (22.5-25.4)	3.44 (87.4)									
	23.2 (34.5)	3.57 (90.7)									
5-1/2 (139.7)	20.3-21.4 (30.2-31.8)	3.75 (95.3)	1.00 (25.4)	0.79 (20.1)			Composite/ NBR Elastomer	Composite/ NBR Elastomer	Composite/ NBR Elastomer	Composite/ FKM Elastomer	
	11.5-18.0 (17.1-26.8)	3.92 (99.6)									
	14.0 (20.8)	4.60 (116.8)									
6-5/8 (168.3)	24.0-32.0 (35.7-47.6)	5.38 (136.5)	1.25 (31.8)	1.23 (31.2)	3.14 (79.8)	33.7 (856.0)	Magnum "A-1", Baker #20 or Owen	250°F 8KSI (121°C) (55.2MPa)	250°F 10KSI (121°C) (68.9MPa)	300°F 10KSI (149°C) (68.9MPa)	375°F 10KSI (191°C) (68.9MPa)
7 (177.8)	17.0-23.0 (25.3-29.8)	5.95 (151.1)									
	23.0-35.0 (34.2-52.1)	5.75 (146.1)									
7-5/8 (193.7)	24.0-33.7 (35.7-50.2)	6.25 (158.8)									
8-5/8 (219.1)	28.0-40.0 (41.7-59.5)	7.38 (187.3)	2.13 (54.0)	3.55 (90.2)	4.71 (119.6)	Composite/ NBR Elastomer	Composite/ NBR Elastomer	300°F 5K PSI (149°C) (34.5MPa)	Composite/ NBR Elastomer	350°F 5K PSI (177°C) (34.5MPa)	
9-5/8 (244.5)	32.3-40.0 (48.1-59.5)	8.38 (212.7)	2.75 (69.9)	5.94 (150.9)	6.28 (159.5)						
	43.5-53.5 (64.7-79.6)	8.13 (206.4)									

For more information, and to find a representative near you, visit www.magnumoiltools.com.

Copyright © 2018 Magnum Oil Tools International, Ltd. All Rights Reserved.

July 2, 2018 10:28 AM

This presentation contains proprietary and/or confidential information that is the exclusive and sole property of Magnum Oil Tools International, Ltd. The presentation also includes information that contains intellectual property rights owned by and/or assigned to Magnum Oil Tools International, Ltd. The information from the presentation shall not be disclosed to any third party without express written consent from Magnum Oil Tools International, Ltd. prior to disclosure.